

COOLTECH



COOLTECH is a “Long Life” coolant formulated from an extremely pure monoethylene glycol base and corrosion inhibitors developed from the very latest techniques in materials protection to overcome the corrosion environments. Its unique environment friendly formula is completely free from phosphates, amines, nitrates and boron, providing extended component lifetime through optimal engine cooling. It gives permanent corrosion protection to all metals in the cooling circuit.

SPECIFICATION

- COOLTECH meets all key international specifications established by the major manufactures and complies with the standards:

APPLICATIONS

- COOLTECH is recommended for cooling IC engines in light vehicles, Lorries, public works vehicles, agricultural tractors and stationary engines.
- COOLTECH should be diluted in water before use to provide a ready to use fluid that can be used with ease. The proportion of COOLTECH can be adjusted to obtain the desired protection against frost
- Easy start up at low temperature (-15°C) and regular operating in all seasons:

PROPERTIES

- In the face of increased engine power output and the engine's containment designed to enhance vehicle aerodynamics, a large amount of calories must now be evacuated. At the same time, engines are tuned so as to operate in very specific temperature ranges. COOLTECH has an additive formula that maintains the ideal” cooling characteristics prescribed by manufacturers in order to:
 - Reduce the heat needed to reach optimal working temperature, so achieving rapid delivery of engine performance.
 - Maintain good thermal distribution between the different mechanical parts so as to restrict expansion while retaining operating clearances.
- Eliminate the risks of overheating that would cause parts to deform as well as reduce their mechanical strength.
- Preclude thermal degradation of the lubricant, which would lead to engine deterioration.


TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6, Kolkata Tel Nos. 033 66228200 / 8209, Fax Nos. 033 66228212

Date 01/12

1/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.total.co.in.



COOLTECH



- In the quest to produce lighter weight vehicles, developments in engine design have turned towards the use of very different types of metals, especially light alloys. As these new materials are more sensitive to corrosion, they fully vindicate the development of COOLTECH, incorporating a new generation of additives.
- This new generation of additives:
 - offers an effective solution to the problems of corrosion to all materials used in cooling circuits.
 - provides enhanced protection against cavitations that could pierce linings and damage water pumps.
 - does not endangered any form of deposits that would change the cooling capabilities either by decreasing heat transfer strength or by blocking the circuits
 - Integrates an alkalinity reserve capable of neutralizing acid combustion gases, which inevitably get into the cooling circuit
 - Is not harmful to joints, hoses and plastics, thereby obviating any risk of leaks
 - Uses a novel principle that consumes an infinitesimal amount of additives giving sustained efficiency over a time period far exceeding that available from most products on the market.

TYPICAL CHARACTERISTICS	TEST METHOD ASTM	COOLTECH
COLOUR	VISUAL	Fluorescent Green
Density at 15oC	ASTM D 1122	1.0809
pH	ASTM D 1287	8.4
Freezing temperature (1: 1)	ASTM D 1177	-15

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
 Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6, Kolkata Tel Nos. 033 66228200 / 8209, Fax Nos. 033 66228212

Date 01/12

1/2

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from www.total.co.in.