



TOTAL HI-PERF 4T SPECIAL 20W-40

Oil for 4-stroke gasoline engines

KEY DATA

- | | |
|--|---------------------------|
| ✓ SAE 20W-40 | ✓ INTERNATIONAL STANDARDS |
| ✓ 4-stroke automatic motorcycle engine oil | ✓ API SL Level |
| ✓ Mineral based engine oil | ✓ JASO MA2 |

Applications

**All types of 4-stroke motorcycles with
manual gear operation**

Compatible with catalytic converters

Compatible with lead-free fuels

Customer benefits

TOTAL Hi-Perf 4T Special 20W-40 is specially designed to operate efficiently under extreme conditions. Its exclusive and unique formulation doesn't allow the oil film to break easily, thus providing superior protection in heavy traffic "stop-n-go" conditions. This leads to a distinctly superior performance, which can be felt from the first use itself!

Benefits:

- ✓ **Active prevention of friction:** Reduction of friction between moving parts ensures the users a smooth ride
- ✓ **Eliminates 'aeration'** of lubricant by preventing foam formation and consequently avoids early wear and tear.
- ✓ **Superior gear protection:** the special additives in the oil remain on the gear parts preventing metal-to-metal contact under high pressure conditions and also during frequent gear changes.
- ✓ **HHTS viscosity:** The excellent base oil used provides the oil a High Temperature High Shear stability. This provides users ideal performance under extreme pressure conditions. Engine is protected by optimal maintenance of oil film thickness even in the most extreme load or speed conditions

Characteristics*

Test	Unit	Result
Grade	-	SAE 20W-40
Volumetric mass at 15°C	kg/m ³	879
Kinematic viscosity at 40°C	mm ² /s	126
Kinematic viscosity at 100°C	mm ² /s	15
Viscosity index	-	123
Pour Point	°C	-27
Flash Point	°C	251

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements above. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL ASIA-PACIFIC PTE. LTD.
331 North Bridge Road,
#23-01 Odeon Towers
Singapore 188720

TOTAL HI-PERF 4T SPECIAL 20W-40
Last update of this datasheet: 11/2015

